



15 WATT SERIES PSA15A Wall Plug Adapter Meets CEC and EISA Requirements



Features

- Limited Power Source
- Class B EMI
- EISA Compliant
- Class II Double Insulated
- High Efficiency

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- PDA

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 50mm (1.97in)
- Height: 33.2mm (1.31in)
- Weight: 145g (5.12oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSA15A-050P (2)	5V	0A	3.0A	50mV	±5%		IV
PSA15A-060P (2)	6V	0A	2.5A	60mV	±5%		IV
PSA15A-075P (2)	7.5V	0A	2.14A	75mV	±5%		IV
PSA15A-090P (2)	9V	0A	1.66A	90mV	±5%		IV
PSA15A-120P (2)	12V	0A	1.25A	120mV	±5%		IV
PSA15A-150P (2)	15V	0A	1.0A	150mV	±5%		IV
PSA15A-240P (2)	24V	0A	0.62A	240mV	±5%		IV
PSA15A-480P (2)	48V	0A	0.31A	480mV	±5%		IV

Note: (1) Measured after 30 minutes with by-pass capacitors 0.1uf/10uf at output connector terminal and oscilloscope set at 20 Mhz. (2) Special order item. Minimum order quantity required. Please consult Phihong USA.

Phihong reserves the right to make changes without further notice. Please consult Phihong USA and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

Input Current

0.5A(RMS) max. @ 120VAC

0.25A(RMS) max. @ 240VAC

Leakage Current

0.25mA max. @ all line conditions

Inrush Current (cold)

< 30A for 120VAC at max. load

< 60A for 240VAC at max. load

(Cold start @ ambient 25°C)

Input Power Saving

0.5W maximum at no load

OUTPUT:

Efficiency

≥ 74.4% average efficiency

Hold-up Time

10mS min. @ 120VAC and max. load

Over Current Protection

Output equipped with short circuit protection – auto restart

Over Current Protection

Output equipped with short circuit protection – auto restart

Over Voltage Protection

By Zener Clamping

Short Circuit Protection

Output can be shorted without damage

ENVIRONMENTAL:

Temperature

Operation 0 to +40°C

Non-operation -25 to +75°C

Humidity

Operation 20 to 90%

Emissions

FCC Class B

CISPR 22 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

DC Output Connector

2.1x5.5mm Center Positive Standard

Mating Connector

Kycon KLD-0202-A or equivalent

Dimension Diagram Unit: mm (inch)

