



20-30W Universal 3-Wire Input Desktop Adapter PSAC30U Adapter Meets Energy Star and EISA Requirements



Features

- Low Cost
- EISA Energy Efficiency Compliance
- Class B EMI
- Compact Size
- Non-Vented/Spill-proof
- ENERGY STAR Compliant
- Low Profile Design

Applications

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

Safety Approvals

- CE
- Energy Star
- cUL/UL
- Meeting Cal. Prop. 65

Mechanical Characteristics

- Length: 103.4mm (4.07in.)
- Width: 42mm (1.65in.)
- Height: 28.7mm (1.13in.)
- Weight: 160g (5.64oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple*	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSAC30U-050	5V	0A	4.00A	70mV	±5	ⓧ
PSAC30U-120	12V	0A	2.50A	120mV	±5	ⓧ
PSAC30U-240	24V	0A	1.25A	240mV	±5	ⓧ
PSAC30U-480	48V	0A	0.63A	480mV	±5	ⓧ
PSAC30U-560	56V	0A	0.54A	560mV	±5	ⓧ

Note (*): Measured with by-pass capacitors 0.1uF//10uf at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.8A (RMS) maximum at 120VAC
0.5A (RMS) maximum at 240VAC

In-rush Current
60A maximum at 100VAC
100A maximum at 240VAC

AC Input Frequency
47 to 63Hz

Leakage Current
3.5mA maximum at 254VAC, 50Hz

Input Power Saving
<0.3W maximum

OUTPUT
Output Power
30W

Efficiency
Meets CEC Standard level V, EPA 2.0
78.6% min. at 5V, 83.5% min at 12V, 24V and 56V

ENVIRONMENTAL:

Operating Temperature 0 to 40°C
Storage Temperature -20 to 75°C

Operating Humidity 20 to 90%

EMI

FCC Class B
EN55022 Class B

Immunity

EN61000-4-2	Level 4
EN61000-4-3	Level 2
EN61000-4-4	Level 2
EN61000-4-5	Level 3
EN61000-4-6	Level 2
EN61000-4-8	Level 1
EN61000-4-11	

High-pot Test

Input to output: 3000VAC, 10mA for 1 minute
Input to F.G.: 1500VAC, 10mA for 1 minute

Insulation Resistance

Input to Output: >7M ohm 500VDC
Input to F.G.: >7M ohm 500VDC

Over Current Protection

Auto restart without damage

Over Voltage Protection

160% maximum

Short Circuit Protection

Output can be shorted permanently without damage

MTBF

50K hours min at full load and 25°C ambient

AC Input Connector

IEC C14

DC Output Connector

5.2 x 2.1 x 10mm Center Positive Barrel

Dimension Diagram Unit: mm (inch)

